

Total Power, Versatility and Reliability

orthodrive®

www.de-soutter.com

High performance 275W motor offers unrivalled large bone reaming and sawing capability

orthodrive

orthodrive

The new **orthodrive**[®] system is the latest innovation in high performance large bone power tools from De Soutter Medical. The MBQ high torque rotary handpiece provides the surgeon with ample power even for the most demanding acetabular reaming procedures. The new drill/ream handpiece produces 20% more reaming torque and the powerful dedicated sagittal saw cuts through the hardest of bone with ease and precision.

POWER

- Through continual engineering refinements, including our fourth generation hybrid motor controller and intelligent battery charging technology, we have increased power by a further 20%
- Li-Ion battery technology assures class leading power to weight ratio.

VERSATILITY

- Exceptional system versatility. 15 different rotary attachments, plus 4 different function attachments, including: reciprocating and mini sagittal saws, wire/pin driver and a unique pulse lavage system.
- In-built, quick change drill/ream gearbox eliminates dedicated reaming attachments, reducing cost and weight.
- Optional twin trigger rotary handpiece with instant forward, reverse and unique oscillating drill/tap modes.

RELIABILITY

- Proven system reliability enhanced through continuous engineering developments, including a hermetically sealed hybrid motor controller and unique intelligent battery charging technology.
- New high performance surface finish protects against the most aggressive detergents whilst offering a highly scratch resistant barrier.

Whether your preference is for battery - either aseptic or sterile - or indeed corded power, the **orthodrive**[®] system provides total OR flexibility.







MBQ MODULAR ELECTRIC SYSTEM



MBQ-701

1289884

0 - 1350 rpm 0 - 300 rpm 19 Nm

Ø 4.4 mm

DB DEDICATED ELECTRIC SAW SYSTEM



deSouffer MEDICAL

orthodrive

ECOPULSE[™] PULSE LAVAGE SYSTEM

"ECO friendly"



ECO Pulse pump kits simply "click" into any MBQ rotary handpiece

Up to 60% less clinical waste, helping to conserve valuable hospital storage by up to 50%.



PERFORMANCE

900

Flow rate: variable 0 - 1.10 litres/min* Pulse rate: variable 0 - 1300 pulses/min* * Performance figures dependent on battery type.

| NOZZLES | | | |
|--|--------|------------|--|
| Туре | Length | Order code | |
| Soft tissue less suction | 10 cm | P20-120 | |
| Soft tissue with suction | 10 cm | P20-121 | |
| Bone cleaning with suction | 10 cm | P20-125 | |
| Femoral canal less suction | 25 cm | P20-122 | |
| Femoral canal with suction | 25 cm | P20-123 | |
| Femoral canal (high capacity) with suction | 25 cm | P20-126 | |
| Femoral brush with suction | 25 cm | P20-124 | |
| | | | |



| •• |
|----|
| |
| |

Soft tissue nozzle pattern



| Туре | Order code | Supplied nozzles |
|--|------------|------------------|
| General purpose with suction | P20-700 | P20-121 |
| Hip arthroplasty with suction | P20-701 | P20-121/P20-123 |
| Hip arthroplasty brush with suction | P20-702 | P20-124 |
| General purpose without suction | P20-703 | P20-120 |
| Hip arthroplasty without suction | P20-704 | P20-120/P20-122 |
| Bone cleaning (high pressure) with suction | P20-705 | P20-125 |
| Bone cleaning (high pressure) without suction | P20-706 | P20-125 |
| Hip arthroplasty (high pressure) with suction | P20-707 | P20-125/P20-123 |
| Hip arthroplasty (high pressure) without suction | P20-708 | P20-125/P20-122 |
| | | |

All pump kits are supplied with nozzles and 3 metres of tubing. Suction tubing is supplied with all suction types. All sterile packed pump kits and individual nozzles are supplied 5 per box.

MBQ DRIVES AND ATTACHMENTS

| | Order code | Model | Chuck description | Final drive speed | Cannulation Ø mm |
|---|---------------|-----------------------|---|------------------------------|---------------------|
| DRILLING AND REA | | DAPTO | | specu | 2 mm |
| | | | | | |
| | 15360 | - | 0.5 - 4.0 mm (5/32") keyed | As handpiece | 3.1 |
| a Hits | 15370 | - | 0.5 - 7.4 mm (1/4") keyed | As handpiece | 4.4 |
| | 15380 | - | 0.3 - 3.0 mm (1/8") keyless | As handpiece | 3.1 |
| | 15390 | - | 0.3 - 7.4 mm (1/4") keyless | As handpiece | 4.4 |
| | | | | | |
| = Gin | 15480 | - | Small A.O. Synthes/ASIF | As handpiece | 2.0 |
| _house | 15490 | - | Large A.O. Synthes/Protec | As handpiece | 4.4 |
| | 15530 | - | Hudson | As handpiece | 4.4 |
| - Andrewson - A | 15540 | - | Trinkle | As handpiece | 4.4 |
| · · · · · · · · · · · · · · · · · · · | 15460 | - | Zimmer | As handpiece | 4.4 |
| | 15470 | - | Hudson/Zimmer combi | As handpiece | 4.4 |
| X3 | 17130 | - | Harris | As handpiece | 4.4 |
| | 15500 | - | DHS | As handpiece | 4.4 |
| | | - | | As handpiece | |
| | 18190 | - | Stryker Triathlon® | | - |
| SAWING ATTACHME | 17930 | - | Aesculap Taragon TX | As handpiece | |
| SAWING ATTACHIVE | | | | | |
| | 15560 | NQ-700 | Mini sagittal saw | 0 - 24500 cpm | - |
| | | | Uses S88 type blades | | |
| | 18280 | CQ-710 | Reciprocating saw. | 0 - 12300 cpm | - |
| | | - | Uses S84 type blades | 0 12000 cpm | |
| 112 | 18390 | CQ-711 | Reciprocating saw. Uses S22 type blades | 0 - 12300 cpm | - |
| RADIOLUCENT DRII | | TOP | Uses 522 type blues | | |
| RADIOLOCENT DIT | | TOR | | | |
| - | 15510 | TQ-700 | Accepts radiolucent | As handpiece | - |
| | | | drill attachment | | |
| | | TTACLIN | | | |
| 90° RADIOLUCENT | DRILL A | TIACHN | 1 E N I | | |
| | _ | | | | |
| | | | Uses D56 type | As handpiece | - // |
| | | and the second second | drill bits | | |
| | 17710 | | | | |
| | 17710 | | | | |
| | | | | | |
| WIRE/PIN DRIVERS | | | | | |
| the second se | 17240 | WQ-710 | Wire/Pin Driver 0.7 - 4.0 mm cap. | 0 - 1300 rpm | 4.0 |
| | 17940 | WQ-701 | Variable Wire Driver 0.6 - 2.0 mm cap. | | |
| - | 17940 | PQ-701 | Variable Wire Driver 0.6 - 2.0 mm cap. Variable Pin Driver 1.8 - 3.2 mm cap. | 0 - 1300 rpm 0 - 1300 rpm | 2.0 3.2 |
| | 17950 | PQ-701 PQ-702 | Variable Pin Driver 1.8 - 3.2 mm cap. Variable Pin Driver 2.6 - 4.0 mm cap. | 0 - 1300 rpm 0 - 1300 rpm | 3.2 4.0 |
| | | 1 2 7 02 | | 0 13001011 | 0 |
| | | | | | |
| | | | | | |
| // | Ash | | | | |
| | | | atalogue for range | | |
| | | | aw blades, drill bits, | | |
| | rotary bl | urs and K | WILES. | | |
| | | | | | |
| | | | | | |
| N | | | | | |
| · | | | | | |
| | | | | | |



BATTERY CHARGERS



orthodrive®

shown with aseptic batteries.

The BC-700 Battery Charger requires minimal user input, simply insert battery and the BC-700 will charge, recover and recondition it to its optimum state.

The large touch-screen display with intuitive menu navigation, displays instant battery charge status and condition. Includes a multi-lingual display and other user settings.

The BC-700 also offers a **unique healthcheck facility,** profiling the condition of an individual battery, automatically reconditioning it, to provide optimal capacity. Alternatively, a manual healthcheck can be easily selected. The BC-700 Battery Charger accepts all De Soutter Medical batteries, ensuring total backwards compatibility.



BC-700 MULTI BAY CHARGER AND MODULE OPTIONS

| Charger - Order code | Charger module description | Charger me Order code | For battery type | Mains power cordsets - 3 metres long. | |
|-------------------------|-----------------------------------|--------------------------|------------------|--|----------------------|
| 15700 | Without charger module fitted | - | - | Please specify - Order co | de |
| 16230 | With 4-off CA-703 charger modules | 18120 | AB-703/AB-704 | UK Euro US/Canada | 8290 8300 8310 |
| 16220 | With 4-off CA-700 charger modules | 15750 | SB-703/SB-704 | Australia/New Zealand Swiss | 8320 14700 |

BC-700 charger modules can be quickly and easily changed to suit the batteries being charged.



SINGLE BAY CHARGERS

| Model | Battery type - Order code | For battery type |
|--------|---------------------------|------------------|
| BC-706 | 17990 | SB-703/SB-704 |
| BC-707 | 18000 | AB-703 |
| BC-708 | 18010 | AB-704 |

LITHIUM ION ASEPTIC BATTERIES

Why choose Lithium Ion battery technology

De Soutter Medical Lithium Ion batteries offer the surgical team and sterile services a number of tangible benefits over conventional battery technology.

Key advantages are:

- Li-Ion technology improves battery 'capacity to weight' ratio by around 25% when compared to equivalent NiMH or NiCad chemistries.
- Significantly extends the useable run time of the power tool.
- Eliminates 'memory effect' normally associated with other battery types.
- De Soutter Medical sterile Li-Ion technology readily withstands repeated machine washing and autoclaving.
- Unique **fuel gauge** incorporated within De Soutter Medical Li-Ion batteries allows the surgical team to instantly assess the battery capacity both before and during use.

| ASEPTIC | LITHIUM ION B | ATTERIES | | |
|----------|-----------------|--------------------|---------|-------------------|
| SMALL | BATTERY | | | |
| S | Battery pack | Aseptic housing | | Aseptic shield |
| Model | Description | Order code | Voltage | Capacity mAh |
| AB-703 | Battery pack | 17910 | 10.95V | 2000 |
| AH-703 | Battery housing | 18080 | - | - |
| AS-703 | Battery shield | 18100 | - | - |
| LARGE | BATTERY | | | |
| | Battery pack | Aseptic housing | | Aseptic shield |
| Model | Description | Order code | Voltage | Capacity mAh |
| AB-704 | Battery pack | 17920 | 14.6V | 2000 |
| AH-704 | Battery housing | 18090 | - | - |
| AS-704 | Battery shield | 18110 | - | |
| | | | | |



LITHIUM ION STERILE BATTERIES



STERILE LITHIUM ION BATTERIES

SMALL BATTERY

| S. | Model SB-703 | Order code 17210 | Voltage 13.2V | Capacity mAh 1100 |
|---|-----------------|---------------------|------------------|----------------------|
| LARGE BATTE | ERY | | | |
| | Model | Order code | Voltage | Capacity mAh |
| ALESTAN AND AND AND AND AND AND AND AND AND A | SB-704 | 17220 | 13.2V | 2500 |

0

CORDED DIRECT POWER



Connected to MBQ-701 via corded module.

T

New slim line design. Requires no set-up. Simply connect to the CM-700 Corded Module for instant use.

Mains power cordsets 3 metres long. Please specify from options below.

| UK | Order code 8290 |
|-------------|------------------|
| Euro | Order code 8300 |
| US/Canada | Order code 8310 |
| Australia | Order code 8320 |
| New Zealand | Order code 8320 |
| Swiss | Order code 14700 |

CM-700 Corded module Order code 15720



PS-701

STERILISATION CONTAINERS



ASEPTIC BATTERY STERILISATION SYSTEM

| Set up | Container and insert tray Order code | lnsert tray Order code |
|-------------------------------------|---|---------------------------|
| 3 handpieces plus 9 attachments | 18150 | 17960 |
| 2 handpieces plus 11 attachments | 18160 | 17970 |

STERILE BATTERY STERILISATION SYSTEM

| Set up | Container and insert tray Order code | lnsert tray Order code |
|------------------------------------|---|---------------------------|
| 3 handpieces plus 9 attachments | 16250 | 17110 |

STANDARD CONTAINER

Aluminium container, aluminium lid. Size: 538 mm x 254 mm x 142 mm. DIN compatible.

Lid - Order code 630843 Base - Order code 630833

WIRE CONTAINER

Order code 655073

Accepts both sterile and aseptic insert trays.

STERILE FILTERED CONTAINER

Order code 17410 Accepts standard and wire container plus tray

Filter paper - single use pack of 100 Order code 657243

Security tag, pack of 100 Order code 657253



Sterile indicator label, pack of 100 - Order code 657263

BATTERY STERILISATION BASKET

For SB-703/SB-704 Batteries Order code 17390

Battery insert tray Order code 17400.



UNITED KINGDOM (INTERNATIONAL HEAD OFFICE) De Soutter Medical Limited Halton Brook Business Park, Weston Road Aston Clinton, Aylesbury, Bucks HP22 5WF Tel: +44 (0) 1296 634 000 Fax: +44 (0) 1296 634 033 Email: info@de-soutter.com

AUSTRALIA De Soutter Medical Australia Pty Ltd 2/12-14 Apollo Drive, Hallam Victoria 3803 Tel: +61 (0) 3 9702 4441 Fax: +61 (0) 3 9702 4484 Email: australia@de-soutter.com

AUSTRIA

De Soutter Medical Austria Zweigniederlassung Österreich Dietrichsteingasse 10, A-3400 Klosterneuburg Tel: +43 (0) 676 96 71 770 Fax: +43 (0) 2243 21 656 Email: austria@de-soutter.com

BELGIUM

De Soutter Medical Belgium In De Bruel 30 3620 Lanaken Tel: +32 (0) 89/47 15 37 Fax: +32 (0) 89/70 12 19 Email: belgium@de-soutter.com

FRANCE De Soutter Medical France 949 Avenue du Parc des Expositions 33260 La Teste de Buch Tel: +33 (0) 5 56 54 89 36 Fax: +33 (0) 9 70 61 37 60 Email: france@de-soutter.com

GERMANY De Soutter Medical Germany Niederlassung Deutschland, Kladenfloss D-66625 Nohfelden Tel: +49 (0) 68 52-99 12 46 Fax: +49 (0) 68 52-99 12 47 Email: deutschland@de-soutter.com

ITALY De Soutter Medical Italia Località Fornace SNC 27022 Casorate Primo - PV Tel: +39 (0) 2 9009 4098 Fax: +39 (0) 2 9009 2673 Email: italy@de-soutter.com

NETHERLANDS De Soutter Medical Nederland Gelderlandhaven 2X 3433 PG Nieuwegein Tel: +31 (0) 85 0491480 Fax: +31 (0) 85 0491489 Email: nederland@de-soutter.com

UNITED STATES OF AMERICA De Soutter Medical USA, Inc. 224 Rolling Hill Road, Suite 12A Mooresville, NC 28117 Tel: +1 (704) 655 9040 fax: +1 (704) 987 2035 Email: usa@de-soutter.com



deSoutter For further information on De Soutter Medical powered instruments and cast saw systems please contact the address in your area.